

EMPLEX

BAG SEALING SOLUTIONS

MPS 7500 Series Continuous Band Sealer

The MPS 7500 series are conveyORIZED bag sealers capable of sealing bags of any weight. These sealers can seal bags up to 12 mil / 300 micron in thickness at production rates (6 mil / 150 wide maximum when gusseted). These sealers are also ideal for when the speed of an MPS 6000 series machine is not enough to meet your manufacturing needs. The MPS 7500 comes standard with a S.S. 6" / 150 mm wide x 6' / 1.8 m long, adjustable height, food grade belt conveyor. The sealer and the conveyor each have their own 1/8 hp motors and the speed of the system is electronically synchronized. Designed for 24/7 operation, these sealers are suitable for all production environments.



Electrical:	120 volts, 11 amps.
Infeed Direction:	Right to Left.
Motor:	Variable Speed DC drive.
Seal Throat Depth:	70 mm / 2.75".
Sealing Section:	254 mm / 10" of heating. 254 mm / 10" of cooling.
Variable Speed:	Up to 20 m / 800" per minute.
Sealing Width:	6 mm / 1/4" standard.
Sealer Operation:	Vertical or Horizontal.
Temperature Range:	0-230 degrees C. 0-445 degrees F.
Temperature Controller:	Digital PID autotune

Model	Configuration
MPS 7500	Conveyorized Sealer
MPS 7510	Conveyorized Sealer with Front End Trimmer
MPS 7520	Conveyorized Sealer with Emboss Coder
MPS 7530	Conveyorized Sealer with Dry Ink Printer
MPS 7550	Conveyorized Sealer with Front End Trimmer & Dry Ink Printer
MPS 7560	Conveyorized Sealer with Front End Trimmer & Emboss Coder

Telephone: 416-291-8085
Toll Free: 800-265-1775
Fax: 416-298-4328
Email: info@plexpack.com
www.plexpack.com

PLEXPACK



PLEXPACK Machinery Distributed By:

Distribuidor: International Coffee Expert
sales@internationalcoffeeexpert.com
www.internationalcoffeeexpert.com